

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number  
WO 2004/020276 A1

- (51) International Patent Classification<sup>7</sup>: B63B 39/06
- (21) International Application Number: PCT/NL2003/000602
- (22) International Filing Date: 28 August 2003 (28.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
1021346 28 August 2002 (28.08.2002) NL
- (71) Applicant (for US only): VAN OOSSANEN & ASSOCIATES B.V [NL/NL]; Sparrenbos 30, NL-6705 BB Wageningen (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): VAN OOSSANEN, Pieter [NL/NL]; Sparrenbos 30, NL-6705 BB Wageningen (NL).
- (74) Agent: VAN WESTENBRUGGE, Andries et al.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VESSEL PROVIDED WITH A FOIL SITUATED BELOW THE WATERLINE



(57) Abstract: Non-planing vessel with single hull (2). A foil (10) is fitted below the waterline at the place where the greatest flow constriction exists, in other words at the transition from the relatively broad part (9) to the narrowing part. This foil is situated at a distance from the hull (2) and preferably extends horizontally over as large a part of the hull as possible at a constant distance from the latter. The foil is designed in such a way that, apart from a lifting force, a forward propelling force is exerted. The performance of the vessel can be improved by fitting such a foil.

WO 2004/020276 A1

BEST AVAILABLE COPY